

## H.264 4CH DVRs

### Description

H.264 4CH Real-time CIF  
 D1/HD1/CIF recording resolution available  
 VGA high definition (1280×1024) output  
 E-zoom and Mouse directed PTZ control  
 3G mobile phone and Email  
 Support 4CH simultaneous playback  
 Independent VGA and CVBS viewing  
 Show "Remaining hours of HDD" information on status bar  
 Support daylight savings time and PIP  
 Support 3 independent coding stream  
 (local, network, mobile)  
 Auto ID (IE or mobile phone)



### Specifications

Model	KTL-4D1/KTL-4D2/KTL-4D3
Channel	4CH
Video Input / Output	NTSC/PAL: BNC 4CH In /1CH Out
Audio Input / Output	4CH RCA Input; 1CH RCA Output
VGA Output	Yes
Display Resolution	NTSC : 720x480; PAL: 720x576
Recording Resolution & Frame Rate	NTSC:120fps@CIF; 120fps@halfD1; 60fps@D1 PAL:100fps@CIF; 100fps@halfD1;50fps@D1
Compression Format	Video:H.264 Compression Audio: G.711
Hard Disk Capacity	Up to 2TB, SATA interface HDD×1
Recording Mode	Manual/ schedule/sensor trigger/motion detection/power-on auto record
Sensors, Alarm	4CH Input, 1CH Output
Network Interface	1 RJ45 10/100Mbps Ethernet
Media Backup	1 USB 2.0 port for USB flash disk, DVD+RW, HDD
PTZ Control	RS-485
IR Remote Control Unit	Yes
USB Mouse	Yes
Operating Temperature	-10℃~+40℃
Power Supply	DC 12V
Dimensions (LxWxH)	315×232×57mm